

Terrazzo Mix

DESCRIPTION:

Terrazzo Mix is a ready to use cementitious materials high quality to be mixed with decorative aggregate such as crushed marble, stones, crushed glass... for resurfacing exterior or interior concrete floors.

ADVANTAGES:

- *Terrazzo Mix* is a pre-bagged high quality material with high compressive strength.
- High abrasion resistance.
- No Shrinkage cracks
- It can be offering with a variety of colors to satisfy all tastes of clients.
- Easy to use and handling.

SHELF LIFE:

Under normal conditions, and when kept dry, the shelf life of *Terrazzo Mix*, is 12 months from the manufacturing date, inventory should be rotated.

PACKAGING:

Terrazzo Mix is available in 25 kg/bag

COVERAGE:

Approximately 1m²/bag at 1.5 mm average thickness when crushed stones had been added to the *Terrazzo Mix* already.

APPLICATION:

- The surface should be clean and free from dust, paint and all lose particles. Dampen the surface before application.
- Mix the material with the same quantity of crushed marble.
- Then mix them with clean water (4.5-5.5 liter/bag)
- Apply the mix directly on a damped substrate on average thickness of 10 – 30 mm.
- Carefully level and smooth the surface by Fresno steel trowel,
- Leave it to cure for minimum of 7 days.
- Smooth the surface by terrazzo concrete floor grinder machine to exposure the aggregate and reach the desired finish.
- Apply aman super sealer to protect the surface.

TECHNICAL PROPERTIES:

Type of blinder	Portland Cement
Filler	Selected aggregate of 1.0mm max
Dry Density	1.6 ± 0.1 kg./Ltr.
Wet Density	About 1.7 ± 0.1 kg/Ltr.
Abrasion resistant	< 95 mm ³
Bonding Strength	> 2 N/mm ²
Compressive Strength	> 45 N/mm ²

GUARANTEE:

The information given in based of knowledge and performance of the material. Every precaution took in the manufacturing of the product and the responsibility is limited to the quality of supplies, with no guarantee of results in the field, as **AMANCRETE** has no control over site conditions or execution of work.